AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-63 (Cancelled)

64. (Previously presented) A method of storing a data set on a storage device having one or more portions of random data, comprising:

determining, using a process dependent upon a user input passphrase, a first storage writing process starting location at a first offset within a portion of random data for initiating a first storage writing process for storing a file index;

determining a second storage writing process starting location at a second offset within a portion of random data for initiating a second storage writing process for storing the data set, said second offset determined using a process that is independent of a process used to generate said first offset;

encrypting the data set;

writing the encrypted data set using the second storage writing process beginning at the second storage writing process starting location in a portion of random data;

creating a file index including an entry in the file index in respect of the data set, the entry comprising an indication of the second storage writing process starting location;

encrypting the file index; and

writing the encrypted file index using the first storage writing process beginning at the first storage writing process starting location in the file of random data.

SUPPLEMENTAL AMENDMENT
U.S. Application No. 10/588,657

Atty. Docket No.: 34-134
Art Unit No.: 2166

65. (Previously presented) A method of operating a computer to store a data set on a storage device, comprising:

determining a first location within the storage device for initiating a first storage writing process for storing a file index;

determining a second storage writing process starting location at a second offset within the storage device for storing the data set, said second offset determined using a process that is independent of a process used to generate said first offset;

encrypting the data set;

writing the encrypted data set using the second storage writing process beginning at the second storage writing process starting location in a portion of random data;

creating a file index including an entry in the file index in respect of the data set, the entry comprising an indication of the second storage writing process starting location;

encrypting the file index; and

writing the encrypted file index using the first storage writing process beginning at the first storage writing process starting location.

66. (Previously presented) The method according to claim 64 in which determining the first storage writing process starting location for creating the file index comprises adding a predetermined offset to the first storage writing process starting location as a beginning of the file index.

67. (Previously presented) The method according to claim 64 wherein the encrypted file index is stored only within the portions of random data on the device.

68. (Previously presented) The method according to claim 64 in which an encrypted file index is stored within one or more portions of random data by writing over random data portions within the storage device with encrypted file index data.

69. (Previously presented) The method according to claim 64 wherein the encrypted data set is stored only within the portions of random data.

70. (Previously presented) The method according to claim 64 in which an encrypted data set is stored within one or more portions of random data by writing over random data portions within the storage device with the encrypted data set.

71. (Previously presented) The method according to claim 64 which further comprises using the user input passphrase for generating a key for encrypting the file index.

72. (Previously presented) The method according to claim 64 in which the passphrase is used for generating a key for encrypting the data set.

73. (Previously presented) The method according to claim 64 in which the passphrase is used in selecting the second storage writing process starting location.

74. (Previously presented) The method according to claim 64 in which at least one of the first location within the file of random data, the second location within the file of random

SUPPLEMENTAL AMENDMENT
U.S. Application No. 10/588,657

Atty. Docket No.: 34-134
Art Unit No.: 2166

data, a key for the file index and a key for the data set is determined by using at least one hash function to operate on the user input passphrase.

75. (Previously presented) The method according to claim 64 in which the passphrase is operated on once to produce an output which is used for determining at least two of the first location within the file of random data, the second location within the file of random data, a key for the file index and a key for the data set.

76. (Previously presented) The method according to claim 64 in which the passphrase is operated on a plurality of times, each operation generating an output for use in determining at least one of the first location within the file of random data, the second location within the file of random data, a key for the file index and a key for the data set.

77. (Previously presented) The method according to claim 64 in which a common key is used for encrypting the data set and for encrypting the file index.

78. (Previously presented) The method according to claim 64 which comprises a step of storing further sets of data using said passphrase.

79. (Previously presented) The method according to claim 78 which is such that a respective location for each data set is selected, each data set is encrypted and stored at the respective location, and respective entries are added to the file index.

SUPPLEMENTAL AMENDMENT
U.S. Application No. 10/588,657

Atty. Docket No.: 34-134
Art Unit No.: 2166

80. (Previously presented) The method according to claim 64, comprising a step of storing further file indexes within the file of random data, each of which indexes is associated with a respective passphrase and each of which indexes is encrypted and is stored at a location selected in dependence on the respective passphrase.

81. (Previously presented) The method according to claim 80 in which respective encryption keys are generated from the respective passphrases and these respective keys are used for encrypting data sets which are associated with each file index.

82. (Previously presented) The method according to claim 80 comprising a step of selecting the passphrase for, and hence location for, an additional file index with knowledge of the respective passphrases corresponding to file indexes already stored in the file of random data such that collisions may be avoided.

83. (Previously presented) The method according to claim 80, in which, where there are a plurality of file indexes stored in the file of random data, the method comprises a step of selecting a location for an additional data set with knowledge of the respective passphrases corresponding to file indexes already stored in the file of random data such that collisions may be avoided.

84. (Previously presented) The method according to claim 80 comprising a step of storing additional data sets using a passphrase whilst in ignorance of at least one other existing passphrase.

85. (Previously presented) The method according to claim 80 comprising a step of storing data sets in a predetermined relationship to a respective file index to help prevent collisions, for example data sets may be stored adjacent to a respective file index, data sets may be stored substantially contiguously to a respective file index, and data sets may be stored at locations close to but after a respective file index.

86. (Previously presented) The method according to claim 64 comprising a step of storing data on a storage device carrying a plurality of files of random data.

87. (Previously presented) The method according to claim 64 in which the file index comprises a message authentication code.

88. (Previously presented) The method according to claim 87 in which the file index comprises a message authentication code of all associated data sets so as to facilitate detection of tampering.

89. (Previously presented) The method according to claim 87 in which the file index comprises a message authentication code of the file of random data in its entirety for use in detecting other usage of the file of random data.

90. (Previously presented) The method according to claim 64 comprising a step of preprocessing the data set prior to encryption.

91. (Previously presented) The method according to claim 64 comprising a step of presenting a user with an indication of a location within the file of random data that will be selected for the file index when using a predetermined passphrase.

92. (Previously presented) The method according to claim 91 comprising a step of accepting user entered trial passphrases and providing a user with an indication of a location within the file of random data that will be selected for the file index for each trial passphrase.

93. (Previously presented) The method according to claim 91 comprising a further step of providing to a user an indication of the regions of the file of random data that are already occupied by file indexes having passphrases that have been supplied by a user.

94. (Previously presented) The method according to claim 64 comprising a step of receiving an indication from a user of a location within the file of random data which a user desires to use for a file index.

95. (Previously presented) The method according to claim 94 comprising the step of suggesting possible passphrases to a user in response to a user indicating a location within the file of random data which a user desires to use for a file index.

96. (Previously presented) The method according to claim 94 comprising steps of receiving a user input passphrase and suggesting a modified passphrase.

97. (Previously presented) The method according to claim 96 in which the modification of the passphrase is selected so as to at least one of: move a location at which an associated index would be stored towards a desired location indicated by a user and strengthen the passphrase.

98. (Previously presented) The method according to claim 64 comprising a step of deleting a data set stored on a storage device.

99. (Previously presented) The method according to claim 98 comprising a step of removing a respective entry from the file index.

100. (Previously presented) The method according to claim 99 in which the step of deleting a data set comprises a step of overwriting the data set with random data as well as removing the entry from the file index.

101. (Previously presented) The method according to claim 98 comprising a step of reorganizing data stored in association with a file index when at least one data set referenced in that file index is deleted.

102. (Previously presented) The method according to claim 100 in which the step of overwriting the data set comprises a step of using at least one random data and encrypted data stored in the file of random data for generating pseudo-random data for overwriting deleted files.

103. (Previously presented) The method according to claim 102 in which the method

comprises a step of using random numbers from the file of random data that would be

overwritten when adding a data set to replace any pseudo-random values previously used'

elsewhere within the file of random data.

104. (Previously presented) A computer storage device for steganographically

concealing stored information, said device configured with at least one storage area having one

or more portions of random data containing a file index and a predetermined data set, wherein

the file index is encrypted and is stored at a first location determined by an algorithmic process

dependent upon a user passphrase, and the data set is encrypted and is stored at a second location

determined using a process that is unconstrained by the process used to determine the first

location, and the file index comprises information indicative of the second location.

105. (Previously presented) The storage device according to claim 104 further including

application software stored thereon for execution by a computer to enable steganographic storage

extraction of data sets in the one or more portions of random data.

106. (Previously presented) The storage device according to claim 104 in which the

passphrase is used to generate a key for at least one of encrypting the file index and encrypting

the data set.

107. (Previously presented) The storage device according to claim 104 further

comprising a software application stored by the storage device, the software comprising

1452126

SUPPLEMENTAL AMENDMENT
U.S. Application No. 10/588,657

Atty. Docket No.: 34-134
Art Unit No.: 2166

instructions that when loaded and executed by a computer cause the computer to perform at least

one of the following operations:

accepting a plurality of user input passphrases and generating corresponding

encryption/decryption keys;

determining respective storage writing process starting locations for a plurality of storage

of file indexes;

encrypting a plurality of file indexes;

encrypting a plurality of data sets;

storing a plurality of file indexes;

determining respective storage writing process starting locations for storing a plurality of

data sets;

storing a plurality of data sets;

accepting one or more user input passphrases and using said one or more user input

passphrases for locating and decrypting respective file indexes;

locating one or more encrypted data sets stored within the storage device;

decrypting one or more encrypted data sets stored within the storage device ; and

outputting one or more decrypted data sets stored within the storage device as an

encrypted data set.

108. (Previously presented) The storage device according to claim 104 further including

a conventional file allocation table stored thereon.

SUPPLEMENTAL AMENDMENT
U.S. Application No. 10/588,657

Atty. Docket No.: 34-134
Art Unit No.: 2166

109. (Previously presented) The storage device according to claim 104 wherein at least a portion of the device comprises a Read Only Memory (ROM).

110. (Previously presented) The storage device according to claim 108 further comprising a Read Only Memory (ROM) portion wherein is stored the file allocation table, the software and an operating system header file.

111. (Previously presented) The storage device according to claim 104 wherein the device is operable as a removable storage device.

112. (Previously presented) The storage device according to claim 104 wherein the device is assigned a particular identifying serial number.

113. (Previously presented) The storage device according to claim 104 further including a unique hard coded identifier data stored in memory contained therein, said identifier data for use by a computer for at least one of:

a) an encryption process used for encrypting at least one of the file index and the data; and

b) a decryption process used for decrypting at least one of the file index and the data.

114. (Previously presented) The storage device according to claim 104 wherein the storage device has the appearance of a conventional portable memory storage device.

115. (Currently amended) A computer ~~arranged~~ configured under ~~the~~ control of ~~software~~ computer executable program code, said ~~computer executing software~~ program code including instructions for configuring the computer to steganographically ~~storing~~ store a data set ~~on a storage device~~ within one or more portions of random data contained on ~~said~~ a digital data storage device[[,]] coupled to said ~~computer~~ computer, comprising:

first storage writing process programmable logic circuitry configured to determine a first starting location within a portion of random data on the storage device for initiating a first storage writing process for storing a file index;

second storage writing process programmable logic circuitry configured to determine a second storage writing process starting location ~~at a second offset~~ within a portion of random data on the storage device for storing the data set;

data set encryption programmable logic circuitry configured to encrypt the data set;

data set storing programmable logic circuitry configured to write ~~the~~ an encrypted data set using the second storage writing process beginning at the second storage writing process starting location ~~in a portion of random data~~;

file index programmable logic circuitry configured to create a file index including an entry in the file index in respect of the data set, the entry comprising an indication of a memory location within the storage device of the second storage writing process starting location;

file index encryption programmable logic circuitry configured to encrypt the file index; and

file index storing programmable logic circuitry configured to write ~~the~~ an encrypted file index using the first storage writing process beginning at the first ~~storage writing process~~ starting location ~~in the file of random data~~.

1452126

116. (Currently amended) The computer according to claim 115 further comprising file

index location indicating programmed logic circuitry configured by said software to provide a

user with ~~an~~ a visual indication of a location within ~~a~~ the portion of random data ~~that will~~

determined by said first storage writing process programmable logic circuitry to be used for

storing the file index ~~corresponding to~~ when a particular passphrase is input by a user.

117. (Currently amended) The computer according to claim 115 ~~which is arranged~~

~~under the control of software~~ further comprising passphrase input processing programmed logic

circuitry configured to accept user entered trial passphrases and provide a user with an indication

of a location within ~~the file~~ a portion of random data ~~that will be selected~~ determined for storing

the file index for each trial passphrase entered by a user.

118. (Currently amended) The computer according to claim 115 ~~which is arranged~~

~~under the control of software~~ further comprising file index location programmed logic circuitry

configured to provide a user an indication of regions of ~~the file~~ portions of random data that are

already occupied by file indexes ~~having~~ associated with passphrases ~~that have been~~ supplied by a

user.

119. (Currently amended) The computer according to claim 115 ~~which is arranged~~

~~under the control of software~~ further comprising passphrase suggestion programmed logic

circuitry configured to suggest possible passphrases to a user in response to a user indicating a

location within ~~the file~~ a portion of random data which a user desires to use for storing a file

index.

120. (Currently amended) The computer according to claim 116 ~~which is arranged under the control of software~~ further comprising user interface programmed logic circuitry configured to ~~present~~ provide a user interface for displaying the visual indications on a display device connected to the computer.

121. (Currently amended) The computer according to claim 120 in which the user interface ~~is arranged~~ programmed logic circuitry is configured so that a user can use a pointing device to ~~indicate~~ select a location within ~~the file~~ a portion of random data ~~which a user desires~~ to use for storing a file index.

122. (Previously presented) A method of extracting a data set steganographically stored on a storage device having one or more portions random data containing a file index and a predetermined data set , wherein the file index is encrypted and is stored at a first location determined by an algorithmic process dependent upon a user input passphrase, and the data set is encrypted and is stored at a second location determined using a process that is unconstrained by the process used to determine the first location, and the file index comprises information indicative of the second location, comprising:

using a user input passphrase to determine a location for a file index based upon the user input passphrase;

decrypting the file index;

identifying a location of a data set from the decrypted file index; and

decrypting the data set stored at the identified location.

123. (Previously presented) A computer arranged under the control of software to extract data using The method according to claim 122.

124. (Previously presented) A method of storing a data set on a storage device, comprising:

determining a first location within the storage device for initiating a first storage writing process for storing a file index;

determining a second storage writing process starting location at a second offset within the storage device for storing the data set, said second offset determined using a process that is independent of a process used to generate said first offset;

encrypting the data set;

writing the encrypted data set using the second storage writing process beginning at the second storage writing process starting location in a portion of random data;

creating a file index including an entry in the file index in respect of the data set, the entry comprising an indication of the second storage writing process starting location;

encrypting the file index; and

writing the encrypted file index using the first storage writing process beginning at the first storage writing process starting location, wherein the method further comprises , prior to a user finalizing the user input passphrase, accepting input of at least one user input trial passphrase and providing a user with an indication of a location within the portion of random data that will be determined for creating a file index associated with the at least one user input trial passphrase.

125. (Previously presented) A computer readable data storage medium, said storage medium storing a computer program comprising code portions which when executed a computer cause the computer to perform steps of:

determining a first location within the storage device for initiating a first storage writing process for storing a file index;

determining a second storage writing process starting location at a second offset within the storage device for storing the data set, said second offset determined using a process that is independent of a process used to determine said first offset;

encrypting the data set;

writing the encrypted data set using the second storage writing process beginning at the second storage writing process starting location in a portion of random data;

creating a file index including an entry in the filé index in respect of the data set, the entry comprising an indication of the second storage writing process starting location;

encrypting the file index; and

writing the encrypted file index using the first storage writing process beginning at the first storage writing process starting location in the file of random data.

126. (Currently amended) A method of storing a data set on a <u>computer accessible</u> <u>digital data</u> storage device<u>, comprising:</u> having

<u>initializing</u> one or more portions of a <u>digital</u> data storage area <s>that are initialized</s> <u>of the</u> <u>storage device</u> with random data<u>;</u> <s>comprising the steps of:</s>

determining a first writing process starting location within a data storage portion initialized with random data for creating a file index;

determining a second writing process starting location within a data storage portion

initialized with random data for storing the data set, said second writing process starting location

determined using a process that is unconstrained by a process used to determine said first writing

process starting location;

encrypting the data set;

storing the encrypted data set beginning at the second writing process starting location,

using only data storage portions initialized with random data;

~~making an entry in the~~ creating a file index indicative of which portions of the data

storage device initialized with random data are ~~to be~~ used to store the encrypted data set~~, wherein~~

~~an indication of the second writing process starting location is determinable from the file index~~;

encrypting the file index; and

storing the encrypted file index ~~at the first selected location in the data storage area~~

~~initialized with random data~~ beginning at the first writing process starting location.

127. (Currently amended) The method according to claim 126 ~~wherein the step of~~

~~ensuring that an indication of the second selected location is determinable from the file index~~

~~comprises the step of~~ further comprising:

making an entry in the file index in respect of the data set, the entry comprising an

indication of the second writing process starting ~~selected~~ location.

128. (Currently amended) The method according to claim 126 ~~wherein the step of~~

~~selecting a first location within the data storage area initialized with random data for storing a~~

~~file index, comprises~~

the step of selecting wherein the first writing process starting location from a plurality of

predetermined possible locations within the data storage area initialized with random data, is

determined in dependence on upon one of: of an input received from information provided by a

user; user to a computer accessing the storage device and a selection computing implemented

determining process which is independent of user input.

129. (Currently amended) The method according to claim 126 wherein the step of

selecting a first location within the data storage area initialized with random data for storing a

file, comprises steps of selecting the first writing process starting location in dependence on is

dependent upon a user input passphrase and associating the file index is associated with the user

input passphrase.

130. (Currently amended) The method according to claim 129 wherein said data set is

stored under protection of said user input passphrase and the method comprising a further step of

further comprising:

storing a second data set on the storage device under protection of wherein a writing

process for storing the second data set is dependent upon a second user input passphrase, the step

process of storing the second data set on the storage device comprising steps of:

selecting determining, in dependence on the second user input passphrase, a third writing

process starting location within the a data storage area portion initialized with random data for

storing creating a second file index;

selecting determining a fourth writing process starting location within the a data storage

area portion initialized with random data for storing the second data set;

encrypting the second data set;

storing the encrypted second data set beginning at the fourth ~~selected~~ writing process starting location in ~~the~~ a data storage area initialized with random data;

~~ensuring that an indication of the fourth selected location is determinable from the second file index~~ creating a file index indicative of which portion of the data storage device are used to store the encrypted second data set;

encrypting the second file index; and

storing the encrypted second file index ~~at the third selected location in the data storage area initialized with random data, and comprising, before the step of encrypting the second file index, a further step of recording in the second file index an indication of which parts of the data storage area initialized with random data will be used to store said second data set~~ beginning at the third writing process starting location.

131. (Currently amended) The method according to claim 126 wherein the one or more portions of the data storage area initialized with random data ~~is~~ are reserved only for use in storing data.

132. (Currently amended) The method according to claim 126 wherein one or more portions of the data storage area initialized with random data ~~comprises~~ comprise a file of random data ~~which~~ that is managed by a conventional file system management process on a computer accessing the storage device.

133. (Currently amended) A ~~removable~~ digital data storage device ~~comprising a~~ for concealing stored information, said device having at least one data storage area ~~initialized with~~ containing random digital data, ~~wherein~~ and having a file index and a data set that are steganographically stored in the data storage area ~~initialized with~~ containing random digital data, the file index ~~is~~ being encrypted and ~~stored at a first location~~ located at one or more first storage locations within the data storage area ~~initialized with~~ containing random digital data, the data set ~~is~~ being encrypted and ~~stored at a second location~~ located at one or more second storage locations within the data storage area ~~initialized with~~ containing random digital data, the file index ~~comprises an entry in respect of the data set, the entry comprising an indication of the second location within the data storage area initialized with random data, and the file index comprises an indication of~~ including information for identifying said second storage locations and indicating which parts of the data storage area ~~initialized with~~ containing random digital data are ~~in use~~ being used to store said data set.

134. (Currently amended) A ~~removable~~ digital data storage device ~~carrying~~ on which is stored a software application program and ~~comprising a~~ which includes at least one data storage area initialized with random data, the software application program comprising computer executable code portions which when ~~loaded and run on~~ executed by a computer cause the computer to ~~execute a method of storing a data set on the storage device, the method comprising the steps of:~~

~~selecting a first location within the data storage area initialized with~~ determining one or more first storage locations within the random data to be used for storing a file index;

1452126

~~selecting a second location within the data storage area initialized with~~ determining one or more second storage locations within the random data to be used for storing ~~the~~ a data set, said one or more second storage locations being determined by a process which is not constrained by a process used to determine said one or more first storage locations;

~~encrypting~~ encrypt the data set;

~~storing the~~ sore an encrypted data set at ~~the second selected location in the data storage area initialized with random data~~ one or more of said second storage locations;

~~ensuring that an indication of the second selected location is determinable from the file index~~ create a file index containing information for identifying said one or more second storage locations within the random data and for indicating which parts of the data storage area initialized with random data are being used to store the data set;

~~encrypting~~ encrypt the file index; and

~~storing the~~ store an encrypted file index at ~~the first selected location in the data storage are initialized with random data, and comprising, before the step of encrypting the file index, a further step of recording in the file index an indication of which parts of the data storage area initialized with random data will be used to store said data set~~ said one or more first storage locations.

135. (Previously presented) A method of storing a data set on a storage device having one or more portions of random data, comprising:

determining a first storage writing process starting location at a first offset within a portion of random data for initiating a first storage writing process for storing a data set;

determining a second storage writing process starting location at a second offset within a portion of random data for initiating a second storage writing process that creates a file index, said second offset determined independently from a process used to generate the first offset;

encrypting the data set;

writing the encrypted data set using said first storage writing process beginning at said first storage writing process starting location;

creating a file index having an entry in respect of the data set, the entry comprising at least an indication of the first storage writing process starting location;

encrypting the file index; and

writing the encrypted file index using said second storage writing process beginning at said second storage writing process starting location.

136. (Previously presented) The method of claim 135 wherein said second offset is determined using an algorithm that is dependent upon an input passphrase.